

SENSE

Indoor Air Quality, Energy Monitoring, Workspace Management
Connected



- Particulate Matter
- Carbon Dioxide (CO2)
- Volatile Organic Compounds
- Temperature
- Humidity
- Atmospheric Pressure
- Light
- Noise
- Motion
- Possible customization

Sense continuously monitors air quality to visually alert occupants when it is time to air out to renew the indoor air. With its multi-parameter measurement sensors, Sense is specifically designed to analyze the working environment of your teams. Sense integrates the iZiAiR and iZiFeel air quality and comfort algorithms to more easily study each indoor environment and quickly identify possible improvements. Thanks to its wireless communication module, data can be accessed remotely, simply from a smartphone or a computer screen*.

PRODUCT BENEFITS

- > NDIR CO2 sensor with performance validated by an independent laboratory
- > Compact and design PM1, PM2.5 and PM10 Fine Particle Sensor
- > LED indicator to visualize the air quality level
- > Complete set of sensors for a comprehensive analysis of the indoor environment
- > Anti-theft fixing device for wall mounting
- > Quick and easy installation
- > No maintenance required

APPLICATIONS

- > Monitoring of Indoor Air Quality in tertiary and residential buildings
- > Supervision of ambient parameters at work (offices, meeting rooms)

**Optional subscription fees may apply*

FUNCTIONS

Measurement of Indoor Air Quality

- > Particulate Matters (PM1, PM2.5, PM10)
- > Carbon Dioxide (CO2)
- > Volatile Organic Compounds (VOC)

Measurement of ambient parameters

- > Temperature
- > Relative humidity
- > Atmospheric pressure
- > Light
- > Noise (average and peak levels)
- > Motion / Movement (PIR)

Central button

- > Short press: programmable action
- > Long press: instant measurement and transmission

Local (NFC) or remote (downlink) product configuration and diagnostics

iZiFeelL confort index

iZiAiR Indoor Air Quality Index

Display of CO2 level or Air Quality by indicator light (configurable)



Very good



Average



Warning

SPECIFICATIONS

Particulate Matter (PM1 / PM2.5 / PM10)

Resolution: 0.1 µg/m³

Accuracy: ±15 µg/m³ or ±10% of measuring range

Measurement range: 0 – 2000 µg/m³

Carbon Dioxide (CO2)

Technologie : Dual channel Non-Dispersive InfraRed (NDIR)

Resolution: 1ppm

Accuracy: ±(30 ppm + 3% of measuring range)

Measurement range: 0 – 10000ppm

Total Volatile Organic Compounds (VOCs)

Resolution: 1 µg/m³

Accuracy: ±25%

Measurement range: 0 – 10000 µg/m³

Temperature

Resolution: 0.1°C

Accuracy: ±0.3°C

Measurement range: -30°C / +70°C

Humidity

Resolution: 0.5% R.H.

Accuracy: ±2% R.H.

Measurement range: 0 - 100% R.H.

Atmospheric pressure

Resolution: 1 hPa

Accuracy: ±2.5 hPa

Measurement range: 300 – 1100 hPa

Light

Resolution: 5lux

Accuracy: ± 5lux

Measurement range: 0 – 1000 lux

Noise

Resolution: 1dB

Measurement range: 35 – 120dB

Motion

Technology: Passive InfraRed (PIR)

Angle: 90° (Vertical and Horizontal)

Detection distance: 7m

Frequency of measurements

Every 10 minutes (configurable)

Network pairing / Operation / CO2 indicator

1x RGB LED

Power supply

Powered by USB type-C (5VDC – 1A)

Dimensions: 105 x 105 x 35 mm / **Weight:** 200g

Conditions of use

Indoor environment

Temperature: 0°C to + 50°C

Relative humidity: 0% RH to 95% RH

Lifetime: 10 years

Type of mounting

Wall mounted with anti-theft fixing

Free standing with removable support

Wireless protocol

LoRaWAN – Other wireless protocols studied on request

PRODUCT REFERENCE

SENSE (LoRaWAN) – I655LR

CONTENTS OF THE BOX

- > 1 device
- > 1 anti-theft wall bracket
- > 1 standalone installation bracket
- > 1 AC adapter + 1.80m USB-C cable
- > 2 screws and nylon wall plugs
- > 3M® double-sided adhesive attachment

CERTIFICATION

CE Certification